

MFD 411 DiSEqC 4Sat+1Ter x1out

Art. Number 300495



MFD series DiSEqC 2.0 bi-directional

- DiSEqC 2.0 compatible
- 2 or 4 SAT inputs
- TER in (MFD 411)
- Illuminated LED on the active output
- TRIAX easy mount ABS mast housing

Technical Specifications

ORDER INFORMATION

EAN Number 5702663004955

CHARACTERISTICS

DiSEqC control DiSEqC 2.0

FREQUENCY RANGE

Frequency range SAT | MHz 950...2250 MHz

Frequency range TER | MHz 47...694 MHz

LOSS

Through loss | dB 5.5 (TER: 3.0) dB

ISOLATION

Isolation input A-B | dB 30 dB

ELECTRICAL

Number of positions 4

Switch Type DiSEqC

OPERATIONAL

DC Passthrough Yes (max. 500mA)

DC Current consumption | mA < 40 mA

CONNECTORS



Technical Specifications

Number of inputs	4
Number of outputs	2

MECHANICAL

Product Height mm	57 mm
Product Width mm	140 mm
Product Depth mm	110 mm
Packaging Height m	0.060 m
Packaging Width m	0.140 m
Packaging Depth m	0.120 m
Packaging Volume m ³	0.001 m ³
Net Weight kg	0.241 kg
Tara Weight kg	0.039 kg
Total Weight kg	0.280 kg