



Home&Office Series

HiBoost Hi17-EW

Description

Home&Office Voice+3G wide band booster HiBoost Hi17-EW is designed to improve mobile signal for end users directly. It covers any indoor area up to 1500 square meters and is guaranteed to supply great communication experience with clearer calls and higher mobile data speeds than ever.



Key Features

- Supports EGSM 900 and WCDMA 2100MHz
- Real time LCD display
- Manual and automatic gain control functions
- Self-oscillation protection
- AGC & MGC functions
- Compact and light
- Good heat dissipation for long time operation
- Wide power supply range and low power consumption



Booster Kit Includes


- Voice+3G mobile signal booster
- Outdoor wide band panel antenna
- Indoor wide band panel antenna
- Two 50 ft (15.2m) low-loss HiBoost200 cables
- 12V/3A, AC/DC power supply






Installation Examples

1) Standard Kit (coverage up to 1000 sq.m)



- | | |
|--------------------------------------------------------|-------------------------|
| 1-Outdoor panel antenna +50ft (15.2m) Hiboost200 cable | 2-Mobile signal booster |
| 3-Indoor panel antenna + 50ft (15.2m) Hiboost200 cable | 4-Power supply |

2) Standard Kit + 1 optional Panel/ Omni Kit (+1 indoor panel/omni antenna & splitter – coverage up to 1500 sq.m.)



- | | |
|-------------------------|-----------------------------|
| 1-Outdoor panel antenna | 2-Mobile signal booster |
| 3-Indoor panel antenna | 4-Power supply |
| 5- 2-way splitter | 6-Indoor omni/panel antenna |



Specification

RF Parameter		Uplink	Downlink
Frequency Range	900MHz	880~915MHz	925~960 MHz
	2100MHz	1920~1980MHz	2110~2170 MHz
Max .Gain		65dB	65dB
MGC (Step Attenuation)		≥31dB / 1dB step	
Intelligent AGC*	ALC	≥42dB	
	ISO	≥42dB	
Gain Flatness		Typical≤5dB (P-P)	
Noise Figure @ Max. System Gain		Typical≤5dB	
V.S.W.R		Typical≤2	
Group Delay		≤1μs	
Frequency Stability		≤0.01ppm	
Electrical Parameter			
Power Supply		Input AC100~240V,50/60Hz,Output DC12V/3A	
Power Consumption		≤10W	
Input & Output Impedance		50 ohm	
Indicator			
LCD Display		Frequency, Gain, Output Power, ALC, ISO, etc.	
Mechanical Parameter			
I / O Port Type		N-Female	
Dimension		4.7*7.8*1.3 inch/120*198*34mm	
Weight		≤2.2lbs/1KG	
Environment Parameter			
Operating Temperature		-10°C~+55°C	
Storage Temperature		-10°C~+80°C	
Relative Humidity		5% - 95%	
Barometric Pressure		55 kPa -106 kPa	
Environment Conditions		IP40	

* MGC, ALC and ISO share intelligent AGC 42 dB range.

** ALC: 42dB automatic gain adjustment range to stabilize the output power.

*** ISO: 42dB intelligent isolation processing to avoid self-oscillation.

Note: Typical specification for room temperature.

We reserve the right to change this specification without prior notice.