


Stand alone modulators

DSB TV modulators

- frequency agile double sideband multistandard TV modulators
- LED display and push buttons control of internal microprocessor
- non-volatile channel memory
- PLL crystal stabilization of carriers frequency
- built-in power supply
- adjustable audio input level & RF output level
- protection from unauthorized access
- loop through RF combining
- die-cast housing inside plastic case
- connectors:
 - video/audio - RCA sockets
 - RF - type F

MT41

standards: G/H/I/L/K/M/N/Au (UHF range)

MT47standards: B/G/D/K/H/I/L/M/N/Au
(UHF & VHF ranges)**MT57**standards: B/G/Au/stereo A2,
D/K/H/I/L/M/N/mono (UHF & VHF ranges)**CABRIO LINE**

| Technical specifications | | MT41 | MT47 | MT57 |
|--|--|-------------------------|------------------------------------|-------------------------------------|
| T Y P E | | | | |
| Ordering number | | 12860V1 | 12862V1 | 12863V1 |
| Video input | frequency range | | 20 Hz - 6 MHz | |
| | level/impedance | | 1 V ± 0.1 V/75 Ω | |
| Audio input | frequency range | | 20 Hz - 15 kHz | |
| | level adjustment | 0 ÷ 7 dB | | ±6 dB by 2 dB step |
| | level/impedance/deviation | 775 mV RMS/10 kΩ/50 kHz | 2x775 mV RMS/10 kΩ/50 kHz | 2x775 mV RMS/10 kΩ/50 kHz |
| RF output | level (typical)/impedance | 90 dBμV/75 Ω | | 85 dBμV/75 Ω |
| | level adjustment | | 0 ÷ -20 dB | |
| | output channels according channels charts | G/H/I/L/K/M/N/Au | | B/G/D/K/H/I/L/M/N/Au |
| | frequency range | 470-862 MHz | | 45-84 MHz, 170-300 MHz, 470-862 MHz |
| Sound subcarrier frequency | pr. | | 4.5 MHz, 5.5 MHz, 6.0 MHz, 6.5 MHz | |
| Second sound subcarrier frequency | pr. | - | | 5.742 MHz* |
| Fine tuning range of video carrier frequency | pr. | | ±2.25 MHz max. by 0.25 MHz step | |
| Combining through loss | | 1.5 dB | | 2.5 dB |
| Frequency range of RF combining | | | 5-862 MHz | |
| A/V ratio | pr. | | 12/16 dB | |
| Amplitude modulation depth, typical | | | 81 % | |
| Signal/noise ratio, weighted | | | ≥ 55 dB | |
| Power consumption | | 230 V~ 50/60 Hz 3.5 W | 230 V~ 50/60 Hz 3 W | 230 V~ 50/60 Hz 4 W |
| Operating temperature range | | -10° ÷ + 50° C | | +0° ÷ + 50° C |
| Dimensions/Weight (packed) | | 133x63x39 mm/0.36 kg | | 133x73x39 mm/0.36 kg |

* B/G/Au stereo A2

pr. software control