



CATV range equipment

Optical receiver

- compact optical receiver offering optimal price-performance ratio
- AGC based on optical input level
- 3xLED indication of optical input level
- die-cast housing
- connectors:
RF output and test - type F
optical - SC/APC



Technical specifications	
T Y P E	
Ordering number	
Optical input	OD005P 03801
optical wave lenght	1100-1600 nm
optical input level (AGC range)	-6 ... 0 dBm
optical return loss	> 40 dB
noise current density	≤ 6.5 pA/√Hz
RF output	
frequency range	47-862 MHz
impedance	75 Ω
return loss	≥ 14 dB at 40 MHz-1.5 dB/oct., but not less 10 dB
frequency response	± 0.75 dB
output level (AGC controlled, 4.9% OMI)	106 dBμV
output level (CTB, EN50083-3)*	107 dBμV (42 ch.)
output level (CSO, EN50083-3)*	107 dBμV (42 ch.)
interstage attenuator	0-15 dB
interstage equalizer	0/4/8 dB
loss in test point	-30 ± 0.7 dB
Power consumption	
Operating temperature range	230 V~ 50/60 Hz 7 W
Dimensions/Weight (packed)	-20° ÷ + 50° C
	135x180x52mm/0.7 kg

* output level (CTB, CSO) is measured with 8 dB interstage equalizer

